



Casing Rotators Model Comparison

Specification

Model	BM-CR1500	BM-CR2000	BM-CR2500	BM-CR3000	BM-CR3500	BM-CR4000
Applicable Casing Diameter	800 ~ 1,500mm (27" ~ 4'11")	1,000 ~ 2,000mm (3'3" ~ 6'7")	1,500 ~ 2,500mm (4'11" ~ 8'2")	2,000 ~ 3,000mm (6'7" ~ 9'10")	3,000 ~ 3,500mm (9'10" ~ 11'5")	3,500 ~ 4,000mm (11'5" ~ 13'1")
Torque	2,125 kN.m (1,567,319 lbf.ft), Boost : 2,720 kN.m (2,006,168 lbf.ft)	3,188 kN.m (2,351,344 lbf.ft), Boost : 4,081 kN.m (3,009,986 lbf.ft)	5,156 kN.m (3,802,870 lbf.ft), Boost : 6,600 kN.m (4,867,909 lbf.ft)	7,162 kN.m (5,282,419 lbf.ft), Boost : 9,167 kN.m (6,761,231 lbf.ft)	8,000 kN.m (5,900,496 lbf.ft), Boost : 10,200 kN.m (7,523,133 lbf.ft)	8,250 kN.m (6,084,887 lbf.ft), Boost : 10,560 kN.m (7,788,655 lbf.ft)
Rotation Speed	0 ~ 2.65 rpm	0 ~ 2.25 rpm	0 ~ 2.34 rpm	0 ~ 1.8 rpm	0 ~ 0.9 rpm	0 ~ 1.5 rpm
Extracting Force	211 ton at 320 bar, 4 Hyd.Cylinder (Stroke 750mm / 2'6")	363 ton at 320 bar, 4 Hyd.Cylinder (Stroke 750mm / 2'6")	486 ton at 320 bar, 4 Hyd.Cylinder (Stroke 750mm / 2'6")	532 ton at 320 bar, 4 Hyd. Cylinder (Stroke 750mm / 2'6")	788 ton at 320 bar, 4 Hyd. Cylinder (Stroke 750mm / 2'6")	905 ton at 320 bar, 4 Hyd. Cylinder (Stroke 750mm / 2'6")
Weight	30 ton Approx. (66,139 lb)	42 ton Approx. (92,594 lb)	64 ton Approx. (141,096 lb)	82 ton Approx. (180,779lb)	100 ton Approx. (264,554lb)	120 ton Approx. (264,554lb)
Power Pack	P2616CR / P3816CR (TIERIV) P3616CR (TIER III)	P3816CR (TIERIV) P3616CR (TIER III)	P6125VR (TIERIV) P6025CR (TIER III)	P6125VR (TIER IV) / P6025CR (TIER III)	P6125VR (TIER IV) / P6025CR (TIER III)	P7625CR (TIER T3)

Contact your Authorized BUMA Equipment Dealer



sales@rocequipment.com

801-214-6127

www.rocequipment.com